

HIT-RE 500 V3

Safety information for 2-Component-products

Issue date: 13/05/2020

Revision date: 13/05/2020

Supersedes: 26/02/2019

Version: 2.3

SECTION 1: Kit identification

1.1 Product identifier

Product name

HIT-RE 500 V3



Product code

BU Anchor

1.2 Details of the supplier of the Safety information for 2-Component-products

Hilti (New Zealand) Ltd.
Level 1, Building B 600 South Road
Ellerslie
1051 Auckland - New Zealand
T +64 9 571 9995
, 800 444 584 toll free - F +64 9526 7780
servicenz@hilti.com

SECTION 2: General information

Storage

Storage temperature : 5 - 25 °C

A SDS for each of these components is included. Please do not separate any component SDS from this cover page

This Kit should be handled in accordance with good laboratory practices and appropriate personal protective equipment should be used

SECTION 3:

Classification of the Product

2.1. Classification of the substance or mixture

ECOTV-C
ACOR-5
SKCO-1B
EYDA-1
SESK-1
GCMU-2
TORE-1B
AECH-2

9.3C: Ecotoxicity to terrestrial vertebrates C
6.1E: Acute Tox. 5 (Oral)
8.2B: Skin Corr. 1B
8.3A: Eye Dam. 1
6.5B: Skin Sens. 1
6.6B: Muta. 2
6.8A: Repr. 1B
9.1B: Aquatic Chronic 2

2.2. Label elements

Hazard pictograms (GHS NZ)



GHS05



GHS07



GHS08



GHS09

Signal word (GHS NZ)

Danger

Hazard statements (GHS NZ)

H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H341 - Suspected of causing genetic defects.
H360 - May damage fertility or the unborn child.
H411 - Toxic to aquatic life with long lasting effects.

HIT-RE 500 V3

Safety information for 2-Component-products

Precautionary statements (GHS NZ)


H433 - Harmful to terrestrial vertebrates
 P280 - Wear eye protection, protective clothing, protective gloves.
 P262 - Do not get in eyes, on skin, or on clothing.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
 P337+P313 - If eye irritation persists: Get medical advice/attention.
 P302+P352 - IF ON SKIN: Wash with plenty of water/...

2.3. Other hazards not contributing to the classification

No additional information available

Additional information

2-component-foilpack, contains:
 Component A: Epoxy resin, Reactive diluent, inorganic filler
 Component B: Amine hardener, inorganic filler



Name	General description	Quantity	Unit	Classification according to the United Nations GHS
HIT-RE 500 V3, B		1	pcs	Acute Tox. 5 (Oral), H303 Skin Corr. 1B, H314 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
HIT-RE 500 V3, A		1	pcs	Skin Corr. 1C, H314 Skin Sens. 1, H317 Muta. 2, H341 Repr. 1B, H360 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

SECTION 4: General advice

General advice

For professional users only

SECTION 5: Safe handling advice

General measures

Spilled material may present a slipping hazard

Environmental precautions

Prevent entry to sewers and public waters
 Notify authorities if liquid enters sewers or public waters
 Avoid release to the environment
 Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations.
 After curing, the product can be disposed of with household waste.

Storage conditions

Protect from sunlight. Store in a well-ventilated place.

Technical measures

Comply with applicable regulations

Precautions for safe handling

Wear personal protective equipment
 Avoid contact with skin and eyes
 Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work
 Avoid contact during pregnancy/while nursing

Methods for cleaning up

This material and its container must be disposed of in a safe way, and as per local legislation
 Mechanically recover the product
 On land, sweep or shovel into suitable containers
 Store away from other materials.

For containment

Collect spillage.

HIT-RE 500 V3

Safety information for 2-Component-products

Incompatible materials

Sources of ignition
Direct sunlight

Incompatible products

Strong bases
Strong acids

SECTION 6: First aid measures

First-aid measures after eye contact

Get immediate medical advice/attention.
Immediately rinse with water for a prolonged period while holding the eyelids wide open
Remove contact lenses, if present and easy to do. Continue rinsing.
Consult an eye specialist

First-aid measures after ingestion

Do not induce vomiting
Rinse mouth
Immediately call a POISON CENTER/doctor.

First-aid measures after inhalation

Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact

Wash with plenty of water/...
Take off immediately all contaminated clothing.
Wash contaminated clothing before reuse.
If skin irritation or rash occurs: Get immediate medical advice/attention.

First-aid measures general

Never give anything by mouth to an unconscious person
If you feel unwell, seek medical advice (show the label where possible)

Symptoms/effects

Causes severe skin burns and eye damage.

Symptoms/effects after eye contact

Causes serious eye damage.

Symptoms/effects after inhalation

May cause an allergic skin reaction.

SECTION 7: Fire fighting measures

Firefighting instructions

Use water spray or fog for cooling exposed containers
Exercise caution when fighting any chemical fire
Prevent fire fighting water from entering the environment

Protection during firefighting

Self-contained breathing apparatus
Do not enter fire area without proper protective equipment, including respiratory protection

Hazardous decomposition products in case of fire

Thermal decomposition generates :
Carbon dioxide
Carbon monoxide

SECTION 8: Other information

No data available

HIT-RE 500 V3, B

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Issue date: 13/05/2020

Revision date: 13/05/2020

Supersedes: 26/02/2019

Version: 1.4

SECTION 1: Identification of the hazardous chemical and of the supplier

Product identifier

Product name HIT-RE 500 V3, B
Product form Mixture
Product code BU Anchor

Other means of identification

No additional information available

Relevant identified uses of the substance or mixture and uses advised against

Recommended uses and restrictions For professional users only

Supplier's details

Supplier

Hilti (New Zealand) Ltd.
Level 1, Building B 600 South Road
Ellerslie
1051 Auckland - New Zealand
T +64 9 571 9995
, 800 444 584 toll free - F +64 9526 7780
servicenz@hilti.com

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
86916 Kaufering - Deutschland
T +49 8191 906876
anchor.hse@hilti.com

Emergency number

Schweizerisches Toxikologisches Informationszentrum – 24h Service
+41 44 251 51 51 (international)
+64 9 571 9995
; 800 444 584 toll free

Country	Organisation/Company	Address	Emergency number
New Zealand	National Poisons Centre		0800 623 000

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

ECOTV-C
ACOR-5
SKCO-1B
EYDA-1
SESK-1
STRI-3
AEAH-3
AECH-3

9.3C: Ecotoxicity to terrestrial vertebrates C
6.1E: Acute Tox. 5 (Oral)
8.2B: Skin Corr. 1B
8.3A: Eye Dam. 1
6.5B: Skin Sens. 1
6.1E (Respiratory tract irritant) : STOT SE 3
9.1D: Aquatic Acute 3
9.1C: Aquatic Chronic 3

2.2. Label elements

Hazard pictograms (GHS NZ)



GHS05

GHS07

Signal word (GHS NZ)

Danger

Contains

2-methyl-1,5-pentanediamine; Phenol, styrenated; m-Xylylenediamine; 3-Aminopropyltriethoxysilan; 2,4,6-tris(dimethylaminomethyl)phenol

Hazard statements (GHS NZ)

H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H335 - May cause respiratory irritation.

HIT-RE 500 V3, B

Safety Data Sheet

Precautionary statements (GHS NZ)

H412 - Harmful to aquatic life with long lasting effects.
H433 - Harmful to terrestrial vertebrates

P280 - Wear eye protection, protective clothing, protective gloves.
P262 - Do not get in eyes, on skin, or on clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P302+P352 - IF ON SKIN: Wash with plenty of water/...

2.3. Other hazards not contributing to the classification

No additional information available

SECTION 3: Composition and information of the ingredients of the hazardous chemical

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc.	Classification according to the United Nations GHS (Rev. 4, 2011)
2-methyl-1,5-pentanediamine	(CAS-No.) 15520-10-2	25 - 35	9.3C: Ecotoxicity to terrestrial vertebrates C, H433 3.1D: Flam. Liq. 4, H227 6.1D: Acute Tox. 4 (Oral), H302 6.1D: Acute Tox. 4 (Dermal), H312 6.1D: Acute Tox. 4 (Inhalation:dust,mist), H332 8.2A: Skin Corr. 1A, H314 8.3A: Eye Dam. 1, H318 6.1E (Respiratory tract irritant) : STOT SE 3, H335
Phenol, styrenated	(CAS-No.) 61788-44-1	5 - 10	6.3A: Skin Irrit. 2, H315 6.5B: Skin Sens. 1, H317 9.1D: Aquatic Acute 2, H401 9.1B: Aquatic Chronic 2, H411
m-Xylylenediamine	(CAS-No.) 1477-55-0	5 - <8	9.3C: Ecotoxicity to terrestrial vertebrates C, H433 6.1D: Acute Tox. 4 (Oral), H302 6.1D: Acute Tox. 4 (Inhalation:dust,mist), H332 8.2B: Skin Corr. 1B, H314 8.3A: Eye Dam. 1, H318 6.5B: Skin Sens. 1, H317 9.1D: Aquatic Acute 3, H402 9.1C: Aquatic Chronic 3, H412
2,4,6-tris(dimethylaminomethyl)phenol	(CAS-No.) 90-72-2	1 - 2,5	6.1D: Acute Tox. 4 (Oral), H302 6.3A: Skin Irrit. 2, H315 6.4A: Eye Irrit. 2, H319
3-Aminopropyltriethoxysilan	(CAS-No.) 919-30-2	1 - 2,5	9.3C: Ecotoxicity to terrestrial vertebrates C, H433 6.1D: Acute Tox. 4 (Oral), H302 8.2B: Skin Corr. 1B, H314 6.5B: Skin Sens. 1, H317

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation

Remove person to fresh air and keep comfortable for breathing.

HIT-RE 500 V3, B

Safety Data Sheet

First-aid measures after skin contact	Wash with plenty of water/.... Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get immediate medical advice/attention.
First-aid measures after eye contact	Get immediate medical advice/attention. Immediately rinse with water for a prolonged period while holding the eyelids wide open. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an eye specialist.
First-aid measures after ingestion	Do not induce vomiting. Rinse mouth. Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	Causes severe skin burns and eye damage.
Symptoms/effects after inhalation	May cause an allergic skin reaction.
Symptoms/effects after eye contact	Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

General measures	Spilled material may present a slipping hazard.
Reactivity	Corrosive vapours

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.
EAC code	2X - 2X

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.
------------------	---

6.1.1. For non-emergency personnel

Emergency procedures	Evacuate unnecessary personnel.
----------------------	---------------------------------

6.1.2. For emergency responders

Protective equipment	Use personal protective equipment as required. Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment. Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. After curing, the product can be disposed of with household waste.

HIT-RE 500 V3, B

Safety Data Sheet

6.3. Methods and material for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. On land, sweep or shovel into suitable containers. Store away from other materials.

SECTION 7: Handling and storage, including how the chemical may be safely used

7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact during pregnancy/while nursing.
Hygiene measures	Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	Comply with applicable regulations.
Storage conditions	Protect from sunlight. Store in a well-ventilated place.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Heat and ignition sources	Keep away from heat and direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

HIT-RE 500 V3, B		
New Zealand	TWA (mg/m ³)	10 mg/m ³
New Zealand	Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 11th Edition

Exposure limit values for the other components

No additional information available

8.2. Monitoring

No additional information available

8.3. Appropriate engineering controls

Appropriate engineering controls	Ensure good ventilation of the work station.
----------------------------------	--

8.4. Individual protection measures, such as personal protective equipment (PPE)

No additional information available

Materials for protective clothing	Long sleeved protective clothing
Hand protection	Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,4		EN 374

HIT-RE 500 V3, B

Safety Data Sheet

Eye protection

Wear security glasses which protect from splashes

Type	Use	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166, EN 170

Skin and body protection

Wear suitable protective clothing



Environmental exposure controls

No specific measures are required provided the product is handled in accordance with the general rules of occupational hygiene and safety.

Consumer exposure controls

Avoid contact during pregnancy/while nursing.

SECTION 9: Physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	red
Odour	Amine-like
Odour threshold	No data available
pH	11.5
Evaporation rate	No data available
Relative evaporation rate (butylacetate=1)	No data available
Melting point / Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	No data available
Flammability (solid, gas)	Non flammable.
Vapour pressure	No data available
Relative density	No data available
Density	Density : 1.31 g/cm ³
Solubility	insoluble in water.
Log Pow	No data available
Viscosity	Viscosity, dynamic : 50 - 70 Pa·s HN-0333
Explosive properties	No data available
Explosive limits	No data available
Minimum ignition energy	No data available

SECTION 10: Stability and reactivity

Reactivity	Corrosive vapours. Corrosive vapours
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No additional information available.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide. Corrosive vapours.

SECTION 11: Toxicological information

HIT-RE 500 V3, B

Safety Data Sheet

11.1. Information on toxicological effects

Acute toxicity (oral)	Oral: May be harmful if swallowed.
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

ATE NZ (oral)	2786.216 mg/kg bodyweight
---------------	---------------------------

2-methyl-1,5-pentanediamine (15520-10-2)

LD50 oral rat	1690 mg/kg (Rat)
LD50 dermal rat	1870 mg/kg
LC50 inhalation rat (mg/l)	4.9 mg/l

Phenol, styrenated (61788-44-1)

LD50 oral rat	> 2500 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat (mg/l)	158.31 mg/l/4h

m-Xylylenediamine (1477-55-0)

LD50 oral rat	1090 mg/kg
LD50 oral	660 mg/kg
LD50 dermal rat	> 3100 mg/kg
LD50 dermal	> 3100 mg/kg
LC50 inhalation rat (Dust/Mist - mg/l/4h)	1.34 mg/l/4h

3-Aminopropyltriethoxysilan (919-30-2)

LD50 oral rat	1.57 ml/kg
---------------	------------

2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)

LD50 oral rat	2169 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 2169 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 2000 mg/kg (Rat; Literature study; Other; >1 ml/kg; Rat; Experimental value)

Skin corrosion/irritation	Causes severe skin burns and eye damage. pH: 11.5
Serious eye damage/irritation	Causes serious eye damage.
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified
Potential adverse human health effects and symptoms	No additional information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water	Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	Harmful to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	Harmful to aquatic life with long lasting effects.
Soil toxicity	Not classified
Terrestrial vertebrate toxicity	Harmful to terrestrial vertebrates.
Terrestrial invertebrate toxicity	Not classified
Other information	Avoid release to the environment.

HIT-RE 500 V3, B

Safety Data Sheet

2-methyl-1,5-pentanediamine (15520-10-2)	
LC50 fish 1	130 mg/l (LC50; 48 h)
LOEC (acute)	1800 mg/l
NOEC (acute)	1000 mg/l
Log Pow	0.27 (Estimated value)
	1870 mg/kg
LD50 oral rat	1690 mg/kg (Rat)
Phenol, styrenated (61788-44-1)	
LC50 fish 1	5.6 mg/l
LC50 other aquatic organisms 1	9.7 mg/l
EC50 Daphnia 1	1.44 mg/l
EC50 72h algae (1)	0.326 mg/l (Algae, Literature study)
NOEC (acute)	3.2 mg/l
BCF fish 2	3246 mg/l
Log Pow	6.24 - 7.77 (Experimental value; OECD 123: Partition Coefficient (1-Octanol/Water): Slow-Stirring Method)
	> 2000 mg/kg
LD50 oral rat	> 2500 mg/kg
Threshold limit algae 1	0.326 mg/l (72 h; Algae)
Threshold limit algae 2	0.14 mg/l (72 h; Algae)
m-Xylylenediamine (1477-55-0)	
LC50 fish 1	75 mg/l
LC50 other aquatic organisms 1	20.3 ppb
EC50 Daphnia 1	15 mg/l
LOEC (chronic)	15 mg/l
NOEC (acute)	10.5 mg/kg
NOEC (chronic)	4.7 mg/l
NOEC chronic crustacea	4.7 mg/l
	> 3100 mg/kg
LD50 oral rat	1090 mg/kg
3-Aminopropyltriethoxysilan (919-30-2)	
LD50 oral rat	1.57 ml/kg
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
LC50 fish 1	> 100 mg/l (96 h; Pisces; Nominal concentration)
LC50 fish 2	70.9 mg/l (96 h; Pisces)
EC50 Daphnia 1	10 - 100 mg/l (Invertebrata; Estimated value)
EC50 other aquatic organisms 1	84 mg/l (72 h; Desmodesmus subspicatus; growth rate; ECHA)
ErC50 (algae)	84 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)
ErC50 (algae)	84 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Desmodesmus subspicatus, Static system, Fresh water, Experimental value, GLP)
NOEC (chronic)	2 mg/l (28 d; activated sludge, domestic; respiration rate; ECHA)
Log Pow	0.77 (Literature; 0.219; Experimental value; Equivalent or similar to OECD 107; 21.5 °C)
Log Koc	1.32 (log Koc, Calculated value)
	> 2000 mg/kg (Rat; Literature study; Other; >1 ml/kg; Rat; Experimental value)
LD50 oral rat	2169 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 2169 mg/kg bodyweight; Rat; Experimental value)
Threshold limit algae 1	10 - 100, Algae
Threshold limit algae 2	84 mg/l (72 h; Scenedesmus subspicatus; Growth rate)

12.2. Persistence and degradability

HIT-RE 500 V3, B	
Persistence and degradability	May cause long-term adverse effects in the environment.

HIT-RE 500 V3, B

Safety Data Sheet

Phenol, styrenated (61788-44-1)	
Biochemical oxygen demand (BOD)	0.000231 g O ₂ /g substance
Chemical oxygen demand (COD)	0.004827 g O ₂ /g substance
m-Xylylenediamine (1477-55-0)	
Not rapidly degradable	

12.3. Bioaccumulative potential

HIT-RE 500 V3, B	
Bioaccumulative potential	Not established.
2-methyl-1,5-pentanediamine (15520-10-2)	
Log Pow	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).
Phenol, styrenated (61788-44-1)	
BCF fish 2	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Bioaccumulative potential	Bioaccumulative potential.
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).

12.4. Mobility in soil

HIT-RE 500 V3, B	
Mobility in soil	No additional information available
2-methyl-1,5-pentanediamine (15520-10-2)	
Log Pow	See section 12.1 on ecotoxicology
Phenol, styrenated (61788-44-1)	
Log Pow	See section 12.1 on ecotoxicology
Ecology - soil	No (test)data on mobility of the substance available.
2,4,6-tris(dimethylaminomethyl)phenol (90-72-2)	
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Ozone	Not classified
Other adverse effects	No additional information available

SECTION 13: Disposal considerations

Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IATA / IMDG / RID	
Other information	No supplementary information available

HIT-RE 500 V3, B

Safety Data Sheet

ADR Regulatory status: Regulated
 IMDG Regulatory status: Regulated
 IATA Regulatory status: Regulated
 RID Regulatory status: Regulated

ADR	IMDG	IATA	RID
14.1. UN number			
3259	3259	3259	3259
14.2. UN proper shipping name			
AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	Amines, solid, corrosive, n.o.s. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)	AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine)
Transport document description			
UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II, (E)	UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II	UN 3259 Amines, solid, corrosive, n.o.s. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II	UN 3259 AMINES, SOLID, CORROSIVE, N.O.S. (2-methyl-1,5-pentanediamine, m-Xylylenediamine), 8, II
14.3. Transport hazard class(es)			
8	8	8	8
14.4. Packing group			
II	II	II	II
14.5. Environmental hazards			
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available			

14.6. Special precautions for user

- Overland transport

Classification code (ADR) C8
 Special provisions (ADR) 274
 Limited quantities (ADR) 1kg
 Packing instructions (ADR) P002, IBC08
 Mixed packing provisions (ADR) MP10
 Transport category (ADR) 2
 Orange plates



Tunnel restriction code (ADR) E
 EAC code 2X

- Transport by sea

Special provisions (IMDG) 274
 Limited quantities (IMDG) 1 kg

HIT-RE 500 V3, B

Safety Data Sheet

Packing instructions (IMDG)	P002
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-B
Stowage category (IMDG)	A
Stowage and segregation (IMDG)	Separated from' acids.
MFAG-No	154

- Air transport

PCA packing instructions (IATA)	859
PCA max net quantity (IATA)	15kg
CAO packing instructions (IATA)	863
Special provisions (IATA)	A3

- Rail transport

Special provisions (RID)	274
Limited quantities (RID)	1kg
Packing instructions (RID)	P002, IBC08
Carriage prohibited (RID)	No

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health, and environmental national regulations specific for the product

HSNO Approval Number	HSNO2618
----------------------	----------

15.2. 15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

SDS Major/Minor	None
Issue date	13/05/2020
Revision date	13/05/2020
Supersedes	26/02/20190

Indication of changes:

Section	Changed item	Change	Comments
2.1	GHS NZ classification	Modified	

HIT-RE 500 V3, B

Safety Data Sheet

Abbreviations and acronyms

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE - Acute Toxicity Estimate
 BCF - Bioconcentration factor
 CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
 DMEL - Derived Minimal Effect level
 DNEL - Derived-No Effect Level
 IATA - International Air Transport Association
 EC50 - Median effective concentration
 IMDG - International Maritime Dangerous Goods
 LC50 - Median lethal concentration
 LD50 - Median lethal dose
 LOAEL - Lowest Observed Adverse Effect Level
 NOAEC - No-Observed Adverse Effect Concentration
 NOAEL - No-Observed Adverse Effect Level
 NOEC - No-Observed Effect Concentration
 PBT - Persistent Bioaccumulative Toxic
 PNEC - Predicted No-Effect Concentration
 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
 RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
 SDS - Safety Data Sheet
 vPvB - Very Persistent and Very Bioaccumulative
 None.

Other information

Full text of H-statements:

3.1D: Flam. Liq. 4	3.1D: Flammable liquids, Category 4
6.1D: Acute Tox. 4 (Dermal)	6.1D: Acute toxicity (dermal), Category 4
6.1D: Acute Tox. 4 (Inhalation:dust,mist)	6.1D: Acute toxicity (inhalation:dust,mist) Category 4
6.1D: Acute Tox. 4 (Oral)	6.1D: Acute toxicity (oral), Category 4
6.1E (Respiratory tract irritant) : STOT SE 3	6.1E (Respiratory tract irritant) : Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
6.1E: Acute Tox. 5 (Oral)	6.1E: Acute toxicity (oral), Category 5
6.3A: Skin Irrit. 2	6.3A: Skin corrosion/irritation, Category 2
6.4A: Eye Irrit. 2	6.4A: Serious eye damage/eye irritation, Category 2
6.5B: Skin Sens. 1	6.5B: Skin sensitisation, Category 1
8.2A: Skin Corr. 1A	8.2A: Skin corrosion/irritation, Category 1A
8.2B: Skin Corr. 1B	8.2B: Skin corrosion/irritation, Category 1B
8.3A: Eye Dam. 1	8.3A: Serious eye damage/eye irritation, Category 1
9.1B: Aquatic Chronic 2	9.1B: Hazardous to the aquatic environment — Chronic Hazard, Category 2
9.1C: Aquatic Chronic 3	9.1C: Hazardous to the aquatic environment — Chronic Hazard, Category 3
9.1D: Aquatic Acute 2	9.1D: Hazardous to the aquatic environment — Acute Hazard, Category 2
9.1D: Aquatic Acute 3	9.1D: Hazardous to the aquatic environment — Acute Hazard, Category 3

HIT-RE 500 V3, B

Safety Data Sheet

9.3C: Ecotoxicity to terrestrial vertebrates C	9.3C: Ecotoxicity to terrestrial vertebrates C
H227	Combustible liquid
H302	Harmful if swallowed.
H303	May be harmful if swallowed
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H433	Harmful to terrestrial vertebrates

SDS_NZ_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

HIT-RE 500 V3, A

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Issue date: 13/05/2020

Revision date: 13/05/2020

Supersedes: 26/02/2019

Version: 1.4

SECTION 1: Identification of the hazardous chemical and of the supplier

Product identifier

Product name HIT-RE 500 V3, A
 Product form Mixture
 Product code BU Anchor

Other means of identification

No additional information available

Relevant identified uses of the substance or mixture and uses advised against

Recommended uses and restrictions For professional users only

Supplier's details

Supplier

Hilti (New Zealand) Ltd.
 Level 1, Building B 600 South Road
 Ellerslie
 1051 Auckland - New Zealand
 T +64 9 571 9995
 , 800 444 584 toll free - F +64 9526 7780
servicenz@hilti.com

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
 Hiltistraße 6
 86916 Kaufering - Deutschland
 T +49 8191 906876
anchor.hse@hilti.com

Emergency number

Schweizerisches Toxikologisches Informationszentrum – 24h Service
 +41 44 251 51 51 (international)
 +64 9 571 9995
 ; 800 444 584 toll free

Country	Organisation/Company	Address	Emergency number
New Zealand	National Poisons Centre		0800 623 000

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

ECOTV-C	9.3C: Ecotoxicity to terrestrial vertebrates C
SKCO-1C	8.2C: Skin Corr. 1C
EYDA-1	8.3A: Eye Dam. 1
SESK-1	6.5B: Skin Sens. 1
GCMU-2	6.6B: Muta. 2
TORE-1B	6.8A: Repr. 1B
AECH-2	9.1B: Aquatic Chronic 2

2.2. Label elements

Hazard pictograms (GHS NZ)



Signal word (GHS NZ)

Danger

Contains

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol ; butanedioldiglycidyl ether ; 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane; trimethylolpropane triglycidylether; [3-(2,3-epoxypropoxy)propyl]trimethoxysilane

Hazard statements (GHS NZ)

H314 - Causes severe skin burns and eye damage.
 H317 - May cause an allergic skin reaction.

HIT-RE 500 V3, A

Safety Data Sheet

Precautionary statements (GHS NZ)

H341 - Suspected of causing genetic defects.
H360 - May damage fertility or the unborn child.
H411 - Toxic to aquatic life with long lasting effects.
H433 - Harmful to terrestrial vertebrates

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear eye protection, protective clothing, protective gloves.
P281 - Use personal protective equipment as required.
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P302+P352 - IF ON SKIN: Wash with plenty of water/...
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - IF exposed or concerned: Get medical advice/attention.
P310 - Immediately call a POISON CENTER/doctor.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P391 - Collect spillage.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards not contributing to the classification

No additional information available

SECTION 3: Composition and information of the ingredients of the hazardous chemical

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc.	Classification according to the United Nations GHS (Rev. 4, 2011)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	(CAS-No.) 1675-54-3	25 - 40	Flam. Liq. Not classified 6.3A: Skin Irrit. 2, H315 6.4A: Eye Irrit. 2A, H319 6.5B: Skin Sens. 1, H317 9.1D: Aquatic Acute 2, H401 9.1B: Aquatic Chronic 2, H411
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	(CAS-No.) 9003-36-5	10-20	6.3A: Skin Irrit. 2, H315 6.5B: Skin Sens. 1, H317 9.1B: Aquatic Chronic 2, H411
butanedioldiglycidyl ether	(CAS-No.) 2425-79-8	5 - 10	9.3C: Ecotoxicity to terrestrial vertebrates C, H433 6.1D: Acute Tox. 4 (Oral), H302 6.1D: Acute Tox. 4 (Dermal), H312 6.1D: Acute Tox. 4 (Inhalation:dust,mist), H332 6.3A: Skin Irrit. 2, H315 8.3A: Eye Dam. 1, H318 6.5B: Skin Sens. 1, H317 9.1D: Aquatic Acute 3, H402 9.1C: Aquatic Chronic 3, H412
trimethylolpropane triglycidylether	(CAS-No.) 30499-70-8	5 - 10	8.2C: Skin Corr. 1C, H314 8.3A: Eye Dam. 1, H318 6.5B: Skin Sens. 1, H317 6.6B: Muta. 2, H341 6.8A: Repr. 1B, H360 9.1B: Aquatic Chronic 2, H411

HIT-RE 500 V3, A

Safety Data Sheet

Name	Product identifier	Conc.	Classification according to the United Nations GHS (Rev. 4, 2011)
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	(CAS-No.) 2530-83-8	2.5 - 5	6.1E: Acute Tox. 5 (Dermal), H313 8.3A: Eye Dam. 1, H318 9.1D: Aquatic Acute 3, H402

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	Gently wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get immediate medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	May cause an allergic skin reaction.
Symptoms/effects after skin contact	Causes skin irritation.
Symptoms/effects after eye contact	Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Water spray. Carbon dioxide. Dry powder. Foam. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

General measures	Spilled material may present a slipping hazard.
------------------	---

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.
EAC code	2X - 2X

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.
------------------	---

HIT-RE 500 V3, A

Safety Data Sheet

6.1.1. For non-emergency personnel

Emergency procedures Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment Use personal protective equipment as required. Equip cleanup crew with proper protection.
Emergency procedures Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment. Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. After curing, the product can be disposed of with household waste.

6.3. Methods and material for containment and cleaning up

For containment Collect spillage.
Methods for cleaning up This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. On land, sweep or shovel into suitable containers. Store away from other materials.

SECTION 7: Handling and storage, including how the chemical may be safely used

7.1. Precautions for safe handling

Precautions for safe handling Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
Hygiene measures Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions Protect from sunlight.
Incompatible products Strong bases. Strong acids.
Incompatible materials Sources of ignition. Direct sunlight.
Heat and ignition sources Keep away from heat and direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

Exposure limit values for the other components

No additional information available

8.2. Monitoring

No additional information available

8.3. Appropriate engineering controls

Appropriate engineering controls No specific measures identified.

8.4. Individual protection measures, such as personal protective equipment (PPE)

No additional information available

HIT-RE 500 V3, A

Safety Data Sheet

Materials for protective clothing

Long sleeved protective clothing

Hand protection

Wear protective gloves. The permeation time is not the maximum wearing time! Generally speaking, it must be reduced. Contact with either mixtures of substances or different substances may shorten the protective function's effective duration.

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	> 0,4		EN 374

Eye protection

Wear security glasses which protect from splashes

Type	Use	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166, EN 170

Skin and body protection

Wear suitable protective clothing



Environmental exposure controls

No specific measures are required provided the product is handled in accordance with the general rules of occupational hygiene and safety.

Consumer exposure controls

Avoid contact during pregnancy/while nursing.

SECTION 9: Physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste.
Colour	Light grey
Odour	characteristic
Odour threshold	No data available
pH	6.6
Evaporation rate	No data available
Relative evaporation rate (butylacetate=1)	No data available
Melting point / Freezing point	No data available
Boiling point	No data available
Flash point	No data available
Auto-ignition temperature	No data available
Flammability (solid, gas)	Non flammable.
Vapour pressure	No data available
Relative density	No data available
Density	Density : 1.45 g/cm ³
Solubility	insoluble in water.
Log Pow	No data available
Viscosity	Viscosity, dynamic : 45 - 59 Pa·s 23 °C
Explosive properties	No data available
Explosive limits	No data available
Minimum ignition energy	No data available

SECTION 10: Stability and reactivity

Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	No additional information available.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.

HIT-RE 500 V3, A

Safety Data Sheet

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)	
LD50 oral rat	> 5000 mg/kg bodyweight (Rat; ECHA)
LD50 dermal rat	> 2000 mg/kg bodyweight (Rat; ECHA)
butanedioldiglycidyl ether (2425-79-8)	
LD50 oral rat	2980 mg/kg (Rat)
LD50 oral	1163 mg/kg (Rat; Exp. Key study ECHA)
LD50 dermal rabbit	1130 mg/kg (Rabbit)
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
LD50 oral rat	8025 mg/kg bodyweight (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	4250 mg/kg bodyweight (Rabbit; Experimental value; Equivalent or similar to OECD 402)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
LD50 dermal rat	> 2000 mg/kg (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)

Skin corrosion/irritation	Causes severe skin burns and eye damage. pH: 6.6
Serious eye damage/irritation	Causes serious eye damage.
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Suspected of causing genetic defects.
Carcinogenicity	Not classified
Reproductive toxicity	May damage fertility or the unborn child.
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified
Potential adverse human health effects and symptoms	No additional information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water	Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Toxic to aquatic life with long lasting effects.
Soil toxicity	Not classified
Terrestrial vertebrate toxicity	Harmful to terrestrial vertebrates.
Terrestrial invertebrate toxicity	Not classified
Other information	Avoid release to the environment.

Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)	
LD50 oral rat	> 2000 mg/kg bodyweight (Rat; ECHA)
LD50 dermal rat	> 5000 mg/kg bodyweight (Rat; ECHA)

HIT-RE 500 V3, A

Safety Data Sheet

butanedioldiglycidyl ether (2425-79-8)	
LC50 fish 1	24 mg/l (96 h; Pisces) ECHA
LC50 other aquatic organisms 1	> 160 mg/l
NOEC (acute)	40 mg/l
Log Pow	-0.15
LD50 dermal rabbit	1130 mg/kg (Rabbit)
LD50 oral rat	2980 mg/kg (Rat)
Threshold limit algae 1	88930 mg/l (96 h; Algae)
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
LC50 fish 1	55 mg/l (96 h; Cyprinus carpio; Young)
LC50 fish 2	237 mg/l (96 h; Salmo gairdneri (Oncorhynchus mykiss))
EC50 Daphnia 1	473 - 710 mg/l (48 h; Daphnia magna)
Log Pow	-0.92 (Estimated value)
LD50 dermal rabbit	4250 mg/kg bodyweight (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LD50 oral rat	8025 mg/kg bodyweight (Rat; Equivalent or similar to OECD 401; Experimental value)
Threshold limit algae 1	119 mg/l (7 days; Anabaena flosaquae)
Threshold limit algae 2	250 mg/l (72 h; Selenastrum capricornutum)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
LC50 fish 1	2.3 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Semi-static system, Fresh water, Experimental value, Nominal concentration)
LC50 fish 2	2.3 mg/l (96 h; Oncorhynchus mykiss; Nominal concentration)
EC50 Daphnia 1	2 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
EC50 72h algae (1)	9.4 mg/l (EPA 660/3 - 75/009, Selenastrum capricornutum, Static system, Fresh water, Experimental value, Biomass)
BCF other aquatic organisms 1	31 (Estimated value, Fresh weight)
Log Pow	3 (Estimated value, 25 °C)
Log Koc	2.65 (log Koc, SRC PCKOCWIN v2.0, QSAR)
	> 2000 mg/kg (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
Threshold limit algae 1	> 11 mg/l (72 h; Scenedesmus sp.)
Threshold limit algae 2	4.2 mg/l (72 h; Scenedesmus sp.)

12.2. Persistence and degradability

HIT-RE 500 V3, A	
Persistence and degradability	May cause long-term adverse effects in the environment.
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol (9003-36-5)	
Not rapidly degradable	
butanedioldiglycidyl ether (2425-79-8)	
Biochemical oxygen demand (BOD)	0.01982 g O ₂ / g substance
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
Not rapidly degradable	
Persistence and degradability	Not readily biodegradable in water.
trimethylolpropane triglycidylether (30499-70-8)	
Not rapidly degradable	

12.3. Bioaccumulative potential

HIT-RE 500 V3, A	
Bioaccumulative potential	Not established.
butanedioldiglycidyl ether (2425-79-8)	
Log Pow	See section 12.1 on ecotoxicology
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
Log Pow	See section 12.1 on ecotoxicology

HIT-RE 500 V3, A

Safety Data Sheet

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
BCF other aquatic organisms 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

HIT-RE 500 V3, A	
Mobility in soil	No additional information available
butanedioldiglycidyl ether (2425-79-8)	
Log Pow	See section 12.1 on ecotoxicology
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane (2530-83-8)	
Log Pow	See section 12.1 on ecotoxicology
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane (1675-54-3)	
Surface tension	59 mN/m (20 °C, 0.09 g/l)
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Ecology - soil	Low potential for adsorption in soil.

12.5. Other adverse effects

Ozone	Not classified
Other adverse effects	No additional information available

SECTION 13: Disposal considerations

Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IATA / IMDG / RID

Other information	No supplementary information available
-------------------	--

ADR Regulatory status: Regulated
 IMDG Regulatory status: Regulated
 IATA Regulatory status: Regulated
 RID Regulatory status: Regulated

ADR	IMDG	IATA	RID
14.1. UN number			
1759	1759	1759	1759
14.2. UN proper shipping name			
CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether)	CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether)	Corrosive solid, n.o.s. (trimethylolpropane triglycidylether)	CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether)
Transport document description			
UN 1759 CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether), 8, III, (E), ENVIRONMENTALLY HAZARDOUS	UN 1759 CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether), 8, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1759 Corrosive solid, n.o.s. (trimethylolpropane triglycidylether), 8, III, ENVIRONMENTALLY HAZARDOUS	UN 1759 CORROSIVE SOLID, N.O.S. (trimethylolpropane triglycidylether), 8, III, ENVIRONMENTALLY HAZARDOUS

HIT-RE 500 V3, A

Safety Data Sheet

ADR	IMDG	IATA	RID
14.3. Transport hazard class(es)			
8	8	8	8
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available			

14.6. Special precautions for user

- Overland transport

Classification code (ADR)	C10
Special provisions (ADR)	274
Limited quantities (ADR)	5kg
Packing instructions (ADR)	P002, IBC08, LP02, R001
Mixed packing provisions (ADR)	MP10
Transport category (ADR)	3
Orange plates	

Tunnel restriction code (ADR)	E
EAC code	2X

- Transport by sea

Special provisions (IMDG)	223, 274
Packing instructions (IMDG)	P002, LP02
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-B
Stowage category (IMDG)	A

- Air transport

PCA packing instructions (IATA)	860
PCA max net quantity (IATA)	25kg
CAO packing instructions (IATA)	864
Special provisions (IATA)	A3, A803

- Rail transport

Special provisions (RID)	274
Packing instructions (RID)	P002, IBC08, LP02, R001
Carriage prohibited (RID)	No

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

HIT-RE 500 V3, A

Safety Data Sheet

SECTION 15: Regulatory information

15.1. Safety, health, and environmental national regulations specific for the product

HSNO Approval Number HSR002542

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

SDS Major/Minor None
 Issue date 13/05/2020
 Revision date 13/05/2020
 Supersedes 26/02/20190

Indication of changes:

Section	Changed item	Change	Comments
9	pH	Added	
14	Transportation information	Modified	
16	Additional information	Added	

Abbreviations and acronyms

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE - Acute Toxicity Estimate
 BCF - Bioconcentration factor
 CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
 DMEL - Derived Minimal Effect level
 DNEL - Derived-No Effect Level
 IATA - International Air Transport Association
 EC50 - Median effective concentration
 IMDG - International Maritime Dangerous Goods
 LC50 - Median lethal concentration
 LD50 - Median lethal dose
 LOAEL - Lowest Observed Adverse Effect Level
 NOAEC - No-Observed Adverse Effect Concentration
 NOAEL - No-Observed Adverse Effect Level
 NOEC - No-Observed Effect Concentration
 PBT - Persistent Bioaccumulative Toxic
 PNEC - Predicted No-Effect Concentration
 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
 RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
 SDS - Safety Data Sheet
 vPvB - Very Persistent and Very Bioaccumulative

Other information

None.

Full text of H-statements:

6.1D: Acute Tox. 4 (Dermal)	6.1D: Acute toxicity (dermal), Category 4
6.1D: Acute Tox. 4 (Inhalation:dust,mist)	6.1D: Acute toxicity (inhalation:dust,mist) Category 4
6.1D: Acute Tox. 4 (Oral)	6.1D: Acute toxicity (oral), Category 4
6.1E: Acute Tox. 5 (Dermal)	6.1E: Acute toxicity (dermal), Category 5

HIT-RE 500 V3, A

Safety Data Sheet

6.3A: Skin Irrit. 2	6.3A: Skin corrosion/irritation, Category 2
6.4A: Eye Irrit. 2A	6.4A: Serious eye damage/eye irritation, Category 2A
6.5B: Skin Sens. 1	6.5B: Skin sensitisation, Category 1
6.6B: Muta. 2	6.6B: Germ cell mutagenicity, Category 2
6.8A: Repr. 1B	6.8A: Reproductive toxicity, Category 1B
8.2C: Skin Corr. 1C	8.2C: Skin corrosion/irritation, Category 1C
8.3A: Eye Dam. 1	8.3A: Serious eye damage/eye irritation, Category 1
9.1B: Aquatic Chronic 2	9.1B: Hazardous to the aquatic environment — Chronic Hazard, Category 2
9.1C: Aquatic Chronic 3	9.1C: Hazardous to the aquatic environment — Chronic Hazard, Category 3
9.1D: Aquatic Acute 2	9.1D: Hazardous to the aquatic environment — Acute Hazard, Category 2
9.1D: Aquatic Acute 3	9.1D: Hazardous to the aquatic environment — Acute Hazard, Category 3
9.3C: Ecotoxicity to terrestrial vertebrates C	9.3C: Ecotoxicity to terrestrial vertebrates C
Flam. Liq. Not classified	Flammable liquids Not classified
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H313	May be harmful in contact with skin
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H341	Suspected of causing genetic defects.
H360	May damage fertility or the unborn child.
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H433	Harmful to terrestrial vertebrates

SDS_NZ_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.