

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Issue date: 21/02/2025

Revision date: 21/02/2025

Supersedes: 22/11/2021

Version: 2.0

SECTION 1: Identification

1.1 Product identifier

Trade name	CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750
Product form	Mixture
Product code	BU Fire Protection Foam

1.2 Other means of identification

No additional information available

1.3 Recommended use of the chemical and restrictions on use

No additional information available

1.4 Details of manufacturer or importer

Supplier

Hilti (New Zealand) Ltd.
Level 1, Building B 600 South Road Ellerslie
Auckland 1051
New Zealand
T +64 9 571 9995
800 444 584 toll free - F +64 9526 7780
servicenz@hilti.com

Department issuing data specification sheet

Hilti AG
Feldkircherstraße 100
Schaan 9494
Liechtenstein
T +423 234 2111
product.compliance-fire.protection@hilti.com

1.5. Emergency phone number

Emergency number	GBK GmbH Global Regulatory Compliance +49 (0)6132-84463
------------------	--

Country	Organisation/Company	Address	Emergency number
New Zealand	National Poisons Centre		0800 764 766

SECTION 2: Hazard identification

2.1. Classification of the hazardous chemical

HSNO Approval Number	HSR002517
----------------------	-----------

Classification according to the Environmental Protection Authority notices (EPA Hazardous Substances and New Organisms Act 1996)

Aerosol, Category 1	H222;H229
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Respiratory sensitisation, Category 1	H334
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 2	H351
Specific target organ toxicity – Repeated exposure, Category 2	H373

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

2.2. GHS Label elements, including precautionary statements

GHS NZ labelling

Hazard pictograms (GHS NZ)



Signal word (GHS NZ)

Danger

Contains

4,4'-diphenylmethanediisocyanate, isomeres and homologues (10 – 25 %); Reaction products of phosphoryl trichloride and 2-methyloxirane (10 – 25 %)

Hazard statements (GHS NZ)

H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
H351 - Suspected of causing cancer
H373 - May cause damage to organs through prolonged or repeated exposure
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P260 - Do not breathe spray.
P280 - Wear eye protection, protective clothing, protective gloves.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Prevention

Storage

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition and information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc.	Classification according to GHS NZ
4,4'-diphenylmethanediisocyanate, isomeres and homologues	CAS-No.: 9016-87-9	10 – 25	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
Reaction products of phosphoryl trichloride and 2-methyloxirane	CAS-No.: 13674-84-5	10 – 25	Acute Tox. 4 (Oral), H302 Carc. 2, H351 Aquatic Chronic 3, H412
Dimethyl ether (Propellant gas (Aerosol))	CAS-No.: 115-10-6	5 – 10	Flam. Gas 1A, H220 Press. Gas (Comp.), H280

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Name	Product identifier	Conc.	Classification according to GHS NZ
isobutane (Propellant gas (Aerosol))	CAS-No.: 75-28-5	5 – 10	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
propane (Propellant gas (Aerosol))	CAS-No.: 74-98-6	2.5 – 5	Flam. Gas 1A, H220 Press. Gas (Liq.), H280

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
First-aid measures after eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Symptoms caused by exposure

Symptoms/effects after inhalation	Danger of serious damage to health by prolonged exposure through inhalation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause respiratory irritation.
Symptoms/effects after skin contact	Causes skin irritation.
Symptoms/effects after eye contact	Causes serious eye irritation.

4.3. Medical attention and special treatment

Other medical advice or treatment	Treat symptomatically.
-----------------------------------	------------------------

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media	Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	Extremely flammable aerosol.
Explosion hazard	Pressurised container: May burst if heated.
Hazardous decomposition products in case of fire	Toxic fumes may be released. Vapours may form explosive mixture with air.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

6.1.1. For non-emergency personnel

Emergency procedures	Evacuate unnecessary personnel.
----------------------	---------------------------------

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

6.1.2. For emergency responders

Protective equipment	Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up	Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
-------------------------	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe spray. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. May form flammable/explosive vapour-air mixture. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid breathing dust/fume/gas/mist/vapours/spray.
Hygiene measures	Wash hands, forearms and face thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Keep only in the original container in a cool, well ventilated place away from : Keep container tightly closed.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.
Storage temperature	5 – 25 °C
Heat and ignition sources	Keep away from heat and direct sunlight. Keep away from ignition sources.

SECTION 8: Exposure controls and personal protection

8.1. Control parameters - exposure standards

propane (74-98-6)	
New Zealand - Occupational Exposure Limits	
Local name	Propane
Remark (NZ)	Simple asphyxiant – may present an explosion hazard
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 13th Edition
Dimethyl ether (115-10-6)	
New Zealand - Occupational Exposure Limits	
Local name	Dimethylether
WES-TWA (OEL TWA)	766 mg/m ³
	400 ppm

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Dimethyl ether (115-10-6)	
WES-STEL (OEL STEL)	958 mg/m ³
	500 ppm
Regulatory reference	Workplace Exposure Standards and Biological Exposure Indices, 13th Edition

Exposure limit values for the other components

No additional information available

8.2. Monitoring methods

No additional information available

8.3. Engineering controls

Appropriate engineering controls

Ensure good ventilation of the work station.

8.4. Individual protection measures, such as personal protective equipment (PPE)

Personal protective equipment

Protective clothing. Safety glasses. Gloves. Avoid all unnecessary exposure.

Hand protection

Wear suitable gloves tested to EN374. Suitable for short-term work or as a splash guard: Nitrile rubber gloves (> 0.1 mm). In case of permanent product contact:

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	>0,35mm		
Disposable gloves	Butyl rubber	6 (> 480 minutes)	>0,35mm		

Eye protection

Chemical goggles or safety glasses

Skin and body protection

Wear suitable protective clothing

Respiratory protection

Not necessary with sufficient ventilation. Ensure good ventilation of the work station. Open windows during application to ensure natural ventilation. If the occupational exposure limit is exceeded: Wear appropriate mask. (e.g. gas filter type A1-P2 according to EN 14387)

Personal protective equipment symbol(s)



Environmental exposure controls

Avoid release to the environment.

Other information

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

Physical state

Liquid

Appearance

Aerosol.

Colour

Manila

Odour

ether-like odour

Odour threshold

No additional information available

pH

No additional information available

Evaporation rate

No additional information available

Relative evaporation rate (butylacetate=1)

No data available

Melting point / Freezing point

No additional information available

Boiling point

No data available

Flash point

No data available

Auto-ignition temperature

No data available

Flammability

Non flammable.

Vapour pressure

Vapour pressure: 5100 hPa

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Relative density	No additional information available
Density	Density: 1.049 g/cm ³
Solubility	No additional information available
Partition coefficient n-octanol/water (Log Pow)	No data available
Viscosity, dynamic	No data available
Explosive properties	Pressurised container: May burst if heated.
Explosive limits	No additional information available
Minimum ignition energy	No data available

SECTION 10: Stability and reactivity

Reactivity	Extremely flammable aerosol. Pressurised container: May burst if heated.
Chemical stability	Not established.
Possibility of hazardous reactions	Not established.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures.
Incompatible materials	Strong acids. Strong bases.
Hazardous decomposition products	fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Toxicity

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
LD50 oral rat	> 10000 mg/kg (Rat, Literature study, Oral)
LD50 dermal rabbit	> 5000 mg/kg (Rabbit, Literature study, Dermal)
LD50 dermal	9400 mg/kg
LC50 Inhalation - Rat	0.49 mg/l

propane (74-98-6)	
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))

isobutane (75-28-5)	
LC50 Inhalation - Rat [ppm]	> 800000 ppm (15 minutes, Rat, Male / female, Experimental value, Inhalation (gases))

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Suspected of causing cancer.
Reproductive toxicity	Not classified
STOT-single exposure	Not classified

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
------------------------	--

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard	Not classified
-------------------	----------------

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750	
Vaporizer	Aerosol

SECTION 12: Ecological information

12.1. Ecotoxicity

Hazardous to the aquatic environment, short-term (acute)	Not classified
Hazardous to the aquatic environment, long-term (chronic)	Not classified.
Soil toxicity	Not classified
Terrestrial vertebrate toxicity	Not classified
Terrestrial invertebrate toxicity	Not classified

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
LC50 - Other aquatic organisms [1]	> 1000 mg/l (96 h, Literature study)
BCF - Fish [1]	268.1 l/kg (BCFBAF v3.01, Estimated value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	10.46 (Calculated, KOWWIN)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	9.078 – 10.597 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
LD50 dermal rabbit	> 5000 mg/kg (Rabbit, Literature study, Dermal)
LD50 oral rat	> 10000 mg/kg (Rat, Literature study, Oral)

propane (74-98-6)	
Partition coefficient n-octanol/water (Log Pow)	1.1 – 2.8 (Experimental value, 20 °C)

Dimethyl ether (115-10-6)	
LC50 - Fish [1]	> 4100 mg/l (NEN 6504: Water - Determination of toxicity with Poecilia reticulata, 96 h, Poecilia reticulata, Semi-static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	> 4400 mg/l (NEN 6501: Water - Determination of toxicity with Daphnia magna, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Lethal)
Partition coefficient n-octanol/water (Log Pow)	0.1 (Experimental value)

isobutane (75-28-5)	
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)

12.2. Persistence and degradability

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750	
Persistence and degradability	No additional information available

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
Not rapidly degradable	
Persistence and degradability	Not readily biodegradable in water.

propane (74-98-6)	
Not rapidly degradable	
Persistence and degradability	Readily biodegradable in water.

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Dimethyl ether (115-10-6)	
Persistence and degradability	Non degradable in the soil. Not readily biodegradable in water.
isobutane (75-28-5)	
Not rapidly degradable	
Persistence and degradability	Readily biodegradable in water.
12.3. Bioaccumulative potential	
CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750	
Bioaccumulative potential	No additional information available
4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
BCF - Fish [1]	268.1 l/kg (BCFBAF v3.01, Estimated value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	10.46 (Calculated, KOWWIN)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	9.078 – 10.597 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
propane (74-98-6)	
Partition coefficient n-octanol/water (Log Pow)	1.1 – 2.8 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Dimethyl ether (115-10-6)	
Partition coefficient n-octanol/water (Log Pow)	0.1 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
isobutane (75-28-5)	
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
12.4. Mobility in soil	
CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750	
Mobility in soil	No additional information available
4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
Surface tension	No data available in the literature
Partition coefficient n-octanol/water (Log Pow)	10.46 (Calculated, KOWWIN)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	9.078 – 10.597 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Adsorbs into the soil.
propane (74-98-6)	
Surface tension	No data available in the literature
Partition coefficient n-octanol/water (Log Pow)	1.1 – 2.8 (Experimental value, 20 °C)
Ecology - soil	Not applicable (gas).
Dimethyl ether (115-10-6)	
Surface tension	No data available in the literature

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Dimethyl ether (115-10-6)	
Partition coefficient n-octanol/water (Log Pow)	0.1 (Experimental value)
Ecology - soil	Not applicable (gas).
isobutane (75-28-5)	
Surface tension	No data available in the literature
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 (Experimental value, 20 °C)
Ecology - soil	Not applicable (gas).

12.5. Other adverse effects






Ozone	Not classified
Other adverse effects	No additional information available

SECTION 13: Disposal considerations

Waste treatment methods	Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Ecological information	Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document description				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
14.3. Transport hazard class(es)				
2.1	2.1	2.1	2.1	2.1
				
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

14.6. Special precautions for user

Overland transport

Classification code (ADR)	5F
Special provisions (ADR)	190, 327, 344, 625
Limited quantities (ADR)	1I
Packing instructions (ADR)	P207, LP02
Mixed packing provisions (ADR)	MP9
Transport category (ADR)	2
Tunnel restriction code (ADR)	D

Transport by sea

Special provisions (IMDG)	63, 190, 277, 327, 344, 959
Limited quantities (IMDG)	SP277
Packing instructions (IMDG)	P207, LP02
EmS-No. (Fire)	F-D
EmS-No. (Spillage)	S-U
Stowage category (IMDG)	None
MFAG-No	126

Air transport

PCA packing instructions (IATA)	203
PCA max net quantity (IATA)	75kg
CAO packing instructions (IATA)	203
Special provisions (IATA)	A145, A167, A802

Inland waterway transport

Classification code (ADN)	5F
Special provisions (ADN)	19, 327, 344, 625
Limited quantities (ADN)	1 L
Excepted quantities (ADN)	E0
Equipment required (ADN)	PP, EX, A
Ventilation (ADN)	VE01, VE04
Number of blue cones/lights (ADN)	1

Rail transport

Special provisions (RID)	190, 327, 344, 625
Limited quantities (RID)	1L
Packing instructions (RID)	P207, LP02

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

Hazardous Substances and New Organisms Act

HSNO Approval Number HSR002517

4,4'-diphenylmethanediisocyanate, isomeres and homologues (9016-87-9)	
Hazardous Substances and New Organisms Act	
HSNO Approval Number	HSR003222

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

propane (74-98-6)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001010
----------------------	-----------

Dimethyl ether (115-10-6)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR000995
----------------------	-----------

isobutane (75-28-5)

Hazardous Substances and New Organisms Act

HSNO Approval Number	HSR001003
----------------------	-----------

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Issue date	21/02/2025
Revision date	21/02/2025
Supersedes	22/11/2021

Indication of changes

Section	Changed item	Change	Comments
3		Modified	

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Abbreviations and acronyms

CAS-No. - Chemical Abstract Service number
 ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
 ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
 ATE - Acute Toxicity Estimate
 BCF - Bioconcentration factor
 BLV - Biological limit value
 BOD - Biochemical oxygen demand (BOD)
 CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
 DMEL - Derived Minimal Effect level
 DNEL - Derived-No Effect Level
 EC-No. - European Community number
 EC50 - Median effective concentration
 ED - Endocrine disrupting properties
 EN - European Standard
 IARC - International Agency for Research on Cancer
 IATA - International Air Transport Association
 IMDG - International Maritime Dangerous Goods
 IOELV - Indicative Occupational Exposure Limit Value
 LC50 - Median lethal concentration
 LD50 - Median lethal dose
 LOAEL - Lowest Observed Adverse Effect Level
 N.O.S. - Not Otherwise Specified
 NOAEC - No-Observed Adverse Effect Concentration
 NOAEL - No-Observed Adverse Effect Level
 NOEC - No-Observed Effect Concentration
 vPvB - Very Persistent and Very Bioaccumulative
 WGK - Water Hazard Class
 VOC - Volatile Organic Compounds
 SDS - Safety Data Sheet
 RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
 PNEC - Predicted No-Effect Concentration
 PBT - Persistent Bioaccumulative Toxic
 OEL - Occupational Exposure Limit
 OECD - Organisation for Economic Co-operation and Development
 COD - Chemical oxygen demand (COD)
 ThOD - Theoretical oxygen demand (ThOD)
 TRGS - Technical Rules for Hazardous Substances
 TLM - Median Tolerance Limit
 STP - Sewage treatment plant

Full text of H-statements	
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 1	Aerosol, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2

CF 125-50 / CF 125-5W50 / CF 126 / CF-I 750 B2 / CF-I 750/B2-SV / CF ISO 750

Safety Data Sheet

according to the Hazardous Substances and New Organisms Act (1996)

Full text of H-statements	
Flam. Gas 1	Flammable gases, Category 1
Flam. Gas 1A	Flammable gases, Category 1A
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Resp. Sens. 1	Respiratory sensitisation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H412	Harmful to aquatic life with long lasting effects

SDS_NZ_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.